

FORNAX OUT

- Plastic industrial LED light fitting, with diffuser made of translucent polycarbonate.
- Suitable for industrial indoor and outdoor roofed spaces, warehouses, sports areas, workshops, garages, transport terminals, utility structures and laboratories without a danger of explosion of gases, dust and combustible fumes.
- Resistant to dust, moisture and spouting water.
- The body and the diffuser are made of polycarbonate (PC), increasing resistance against deformation and impact.
- Maximum ambient temperature: $t_a = 50\text{ }^\circ\text{C}$, maximum ambient temperature: $t_a = 25\text{ }^\circ\text{C}$ (version with emergency back-up source for 1 or 3 hours; M1h, M3h).
- Lifetime of 50,000 hours (L90B10).
- Light fitting protection: IP66 & IK10.



HACCP

IP66

230 V
0/50/60
Hz

TECHNICAL INFORMATION

Diffuser: translucent polycarbonate (PC), UV stable, impact-resistant

Body: grey polycarbonate with Al coolers (PC Al), UV stable, impact-resistant

Reflector: steel sheet, white colour (RAL 9003)

Clips: stainless steel + polyamide

Sealing: polyurethane (PUR), foamed body groove




Cable glands: screwed PG 13,5

Distance part: polyamide + 10 % glass fibre

Terminal block: screwless, three-pole (basic version)

Ventilation plug: type BVPB-01 made of polyamide, size M12 x 1.5

Type	Ta. Max (°C)	Luminous flux light fitting (lm)	Power (W)	Efficacy (lm/W)	Net weight (kg)	Luminaire length (mm)
FORNAX OUT 2600	50	2470	16	154	1.5	612
FORNAX OUT 3200	50	2920	19	154	1.5	612
FORNAX OUT 4400	45	4130	27	153	1.7	612
FORNAX OUT 5200	50	4840	31	156	2.9	1172
FORNAX OUT 6400	50	5880	37	159	2.9	1172
FORNAX OUT 8800	45	8190	51	161	3	1172
FORNAX OUT 12800	35	13160	84	157	3	1172
FORNAX OUT 6500	50	6000	38	158	3.8	1452
FORNAX OUT 8000	50	7290	46	158	3.9	1452
FORNAX OUT 11000	45	11330	71	160	3.9	1452
FORNAX OUT 16000	35	16500	104	159	3.9	1452



OPTIONAL FEATURES

- System connectors: Canalis, Stucchi, Wieland
- DALI adapter: Digital dimmable driver
- M1h & M3h: Back-up power for emergency illumination (1 or 3 hours)
- Dual input ports
- Additional through-wiring (1-, 3- or multi-phase)
- Side hanger for wall mounting and positioning
- Protective metal grid